

BUILD WITH THE BEST

CONSTRUCTION

NABAKI AFRIKA

Professional Building Solutions

CONSTRUCTION-2

SEALANTS & ADHESIVES

PROTECTIVE COATINGS

p1

SEALANTS & JOINTING

p2

FILLERS

p3

ADHESIVES

p4

SPECIALISED PRODUCTS

p5

OLD BAG'MYO RD BRANCH
022 2647756

NEW BAG'MYO RD BRANCH
022 2772828

*Suppliers and Distributors
of Professional Building products*

Tel: +255 (22)2775138 Fax: 2775139

Email : info@nabaki.com

PO BOX 11747 Dar es Salaam

Mobile : 07547 65508

www.nabaki.com

PROTECTIVE COATINGS

p1



ANTIRUST: is a superior corrosion resistant primer for coating new metal, galvanized iron and already rusted surfaces. synthetic polymer-based coating, containing anti-corrosive and some corrosion converting additives, which prevent surfaces from rusting.
USES: *Ideal for use on roofs, steel framing, metal poles and gates, handrails, window and doorframes, tanks, farming implements and other interior and exterior surfaces where rust may occur.*

Pack Size: 500ML 1L 5L 20L Buckets - Colours: Grey Red Black
CVR RATE: Approx. 7-10m² per litre per coat



COASTCOTE: is a premium quality, super fast drying, (1min) single pack polyvinyl butyl metal coating.
USES: *is ideal for use on steel framing, metal poles and gates, handrails, window and doorframes, tanks, farming implements and other interior and exterior surfaces where rust may occur. COASTCOTE is also suitable for industrial surfaces, and for surfaces exposed to intermittent saline conditions including Mild Steel, Galv Steel and Aluminium, also ideal for hot metals ie Car Exhausts - Fireplaces etc*

Pack Size: 500ML 1L 5L 20L Buckets - Available in Matt Black only
CVR RATE: Approx. 7-10m² per litre per coat



FACTOR 30 EXTERIOR: is a waterproof wood sealer is a high quality, long-life (up to 36 months), deep penetrating, exterior wood protector for unvarnished hard and softwoods. Due to the product's excellent penetrating properties, good flexibility in the wood is maintained. High UV values
USES: *is ideal for all outdoor surfaces including gates, window frames, garage doors, fences, furniture*

Pack Size: 120ml & 250ml tins - CLEAR
CVR RATE: Approx. 6-8m² per litre per coat



FACTOR 30 INTERIOR: interior polyurethane wood varnish is a high quality, long-life wood protector for previously varnished and unvarnished interior hard and softwoods. For interior use only. High Viscosity - smooth finish - tough & durable.

Pack Size: Packaging Sizes 500ml, 1 liter, 5 liter
CVR RATE: Approx. 8 - 10 m² Per coat depending on porosity of wood.



FACTOR 30 INTERIOR/EXTERIOR: is a high quality, long-life (up to 24 months), wood protector for previously varnished and unvarnished hard and softwoods.
USES: *is ideal for exterior / interior fascias, garage doors, window frames, pergolas, garden furniture, cupboards and interior furniture.*

Pack Size: Packaging Sizes 500ml, 1 liter, 5 liter
CVR RATE: Approx. 8 - 10 m² Per coat depending on porosity of wood.



STOPAQ produce a totally unique and innovative range of products, based on viscous-elastic technology. The solutions are crucial for the long term protection against the damages caused by water infiltration and corrosion. SELF-HEALING VISCO-ELASTIC COATING TECHNOLOGY: Excellent adhesion to any substrate like PE, PP, FBE* Impervious to water and oxygen* Easy and fast to apply, even at cold temperatures * Self-healing ability when slightly damaged* 30 year warranty
USES: The patented STOPAQ products have been widely used throughout the world by major oil and gas, construction, telecommunications, power, wastewater and utility companies.



Pack Size: 310ml/500ml/2000ml
CVR RATE: See Technical Specification

SEALANTS & JOINTING

p2



PERMOMASTIC: is a solvent, rubber based sealant, which has excellent adhesion, strength, flexibility and resists cracking and will form an effective durable seal.

USES: Building sealant • Pipe joint sealing • Primary or secondary concrete joint sealer • Repair of cracks and leaking joints • Manhole joints • Water vapour barrier • Bedding and pointing of window and door frames • Bedding of window sills • Bedding sheet roofing onto structural frames • Bedding flanges in gutters, pipes and duct work • Bedding components in caravan and coach. Building • Sealing lap joints in construction

Pack Size: 310 ml Cartridge/25 kg Bucket—Col: White and Grey
CVR RATE: 5 metres : 6 x 10 mm joint per cartridge



ACRYLIC SEALANT: is a general-purpose, flexible sealant that is used for caulking, grouting, jointing and embedding in building construction. It resists cracking and gives a smooth finish.—paintable

USES: Suitable for internal and external applications and is ideal for use in the following applications: • Suitable for most joints • Flexible crackfiller • Cornices and skirting boards • Sealing of construction Frameworks e.g. window frames, door frames, floorboards, ceilings and roofs

Pack Size: 300 ml Cartridge in White or Grey
CVR RATE: 12 metres : 5 x 6 mm joint per cartridge



BUILD-SILICON: is NEUTRAL CURE SEALANT is a one part sealant, which includes a fungicide. It cures fast and tack free, and has excellent adhesion to most porous and non-porous substrates. It has excellent weatherability and withstands temp extremes -40°C to +100°C.

USES: *is ideal for:* - sealing of connecting and expansion joints - sealing frameworks to construction surfaces (plaster, cement, brick etc) - sealing joints in PVC or polycarbonate sheeting - glazing, curtain walling, sanitary and DIY applications

Pack Size: 310 ml Cartridge Clear or Grey
CVR RATE: 4 metres : 5 x 5 mm joint per cartridge



MS 37: is a new technology, high quality CRYSTAL CLEAR neutral curing, odourless, UV resistant adhesive and sealant in one. It provides excellent adhesion to almost anything, including damp surfaces and can be used for interior and exterior applications. It remains elastic once cured and can be painted immediately.

USES: - Sealing and bonding in the building industry • Sealing between building carpentry and masonry • Sealing of air-conditioning and ventilation joints • Sealing of floor and paving joints and low movement wall joints • Sealing of metal coverings • Sealing cracks in plaster • Sealing containers and refrigeration work • Sealing expansion and movement joints • Weather-sealing between door/window frames and plaster • Joints

Pack Size: 310 ml Cartridge CRYSTAL CLEAR
CVR RATE: 4 metres : 5 x 5 mm joint per cartridge



SIKAFLEX-11FC: is a professional fast curing one-component polyurethane sealant/adhesive with permanent elasticity.

USES: for flexible bondings in particular those subject to impact or vibrations incl : As an elastic adhesive for: Assembling metal framed buildings • Cover plates and coverings • Light-weight construction materials • Acoustic ceiling tiles • Wood, metal or plastic window and door frames. • Floor mouldings and door sills. As an elastic joint sealant for: joints in concrete, epoxy, stone and quarry tiled floors • joints in roofing and guttering, etc • Flexible draught proofing • Containers, water tanks and silos. Bolted lap joints • Sealing penetrations in walls or floors for ducts, piping, etc • Sanitary purposes: air-duct seals - tile bonding - floor joints - caulking - Expansion Joints - Construction Joints - Caulking Joints

Pack Size: 310 ml Cartridge white, grey, black, beige, brown
CVR RATE: One pack of Sikaflex-11 FC will produce the following lengths of bead for various bead diameters (approx. per pack): **310 ml Cartridge:** 3 mm bead 43 metres 3 mm bead 81 metres/



CONFLEX SL/SLG: trafficable grade polyurethanes are 3 part sealants which cure to form a durable, flexible, watertight bond with most building materials capable of dynamic joint movement toalling +25%

USES: Use to seal expansion, control and perimeter joints in parking decks, plazas and malls, patios, driveways, factory & warehouse floors, fuel storage areas, airport traffic areas, runways etc.

Pack Size: 6 Liter Pack Colour: BLACK
CVR RATE: See Product Specifications

FILLERS

p3

ALCOLIN FLEXIFILL is a ready mixed Interior/Exterior polymer-based filler and spackle, easy to use and can be trowelled like a plaster over large areas. It is UV stable, weather resistant, solvent free
USES: adheres permanently to concrete, stone, metal, tiles and wood. ALCOLIN FLEXIFILL can be used internally or externally and dries to a tough, flexible durable finish. Ideal for repairing and filling cracks, holes, imperfections on walls, floors, ceilings and roofs, and for replacing loose

Pack Size: 250ml TUB—Col: Fine WHITE
CVR RATE: Subject to Application

LITEFILL is a revolutionary, ready-mixed polymer-based crackfiller, which is light in weight, and gives a professional smooth finishing a single application, leaving surfaces looking completely flawless.
USES: easy to apply and smooth over... ALCOLIN LITEFILL is ideal for restoring damaged surfaces such as plaster defects and wall cracks to their original look. Suitable for interior and exterior applications, LITEFILL can be used to fill all types of cracks and holes on practically any surface including walls, plaster, cement and wood.

Pack Size: 250ml TUB—Col: Fine WHITE
CVR RATE: Subject to Application

WOODMATE: is a synthetic, siliconised sealant, which locks out water, resists moisture, fungus and mildew, is odour-free.
USES: it is ideal for providing a colour matched waterproof seal between worktops and splash backs, either at the time of installation or to seal existing worktops. Suitable for internal and external applications, and excellent for use in Finishing cupboard joints, joining between counter tops, Sealing between wooden surfaces, walls, cupboards and floors, joints of Wardrobes, worktops, cooking tops, baseboards, etc.

Pack Size: 150/300 ml Cartridges : Pine, Oak and Teak
CVR RATE: 4 metres : 5 x 5 mm joint : per cartridge

FIX ALL: FIX-ALL is a modern, synthetic resin based Universal adhesive paste, which is used in place of nails and screws. It has excellent bonding strength, is fast sticking and eliminates the need for drilling.
USES: excellent for fixing name plates, house numbers, plastic letters, mirrors, decorative frames, dado rails, panels, moldings, skirting boards, wall and floor tiles, cork tiles, stone, window sills, electrical boxes, shoe repairs, etc. is suitable for internal and external applications and adheres to most Construction materials, without the need for priming. Also suitable for use on expanded polystyrene. Typical applications include: • DIY Projects • Construction • Carpentry • Handicraft • Boating

Pack Size: 50 ml Tubes / 300 ml Cartridges
CVR RATE: 12 metres : 5 x 5 mm joint : per cartridge (300ml)

FILLAFOAM is a single part polyurethane expanding foam, which is used to fill, seal and insulate. It cures to a durable, semi-rigid structure, is non-shrinking and has outstanding insulating properties.
USES: Suitable for interior and exterior applications. ALCOLIN FILLAFOAM is weatherproof and damp proof. It is non-toxic and will not expand or decay once cured. Seals out drafts around windows, doors and baseboards • Fills cracks, joints and gaps around pipes, vents

Pack Size: 500ML Can
CVR RATE: 25M PER 500ml CAN

WOOD FILLER is waterbased, ready mixed wood stopping which is fast setting. It can be sanded, drilled and overpainted with most varnishes and paints
USES: For wood filling holes/ cracks in wood. Wide colour range to match the wood

Pack Size: 200g tubes / 10kg containers
CVR RATE: 25M PER 500ml CAN

ADHESIVES

p4

FASTSET: FAST SET WOOD GLUE is high quality fast setting polyvinyl acetate based adhesive (PVA), which dries to form a clear, tough bond which is stronger than wood.
USES: has excellent adhesion to porous substrates: Soft woods e.g. Pine, Meranti • Hard woods e.g. Imbuia, Oak • Processed board e.g. Hardboard, Chipboard, Supawood • Paper and Cardboard. — Veneering—Also bonds felt, cloth, leather, and cork

Pack Size: 250ml / 500ml Bottles with Applicator Nozzles CVR
RATE: 4/M2 PER LITER

ULTRA WOOD GLUE: is the most advanced water-based adhesive available today. It combines the safety, strength, sandability, ease of use and water cleanup of PVA adhesives with the durability, open time and water-resistance of polyurethanes, is the first ever one-part wood glue to pass the ANSIVHPVA

USES: • Waterproof — passes ANSIVHPVA Type 1 specification • Water based formulation — water cleanup, non-toxic, non-flammable (wet state) • No foaming or stained fingers — easy to use, no mess • Long open time — more time for assembling of parts • Fast Setting Speed — shorter press times, increased output • Superior strength — strong final bonds • Low application temperature • Resists solvents, heat and mildew • Unaffected by finishes • Tough Glue line which sands easily • Strong initial tack • FDA approved for indirect food contact

Pack Size: 250ml / 500ml Bottles with Applicator Nozzles CVR
RATE: 200g per m2

PROFESSIONAL WOOD GLUE: is a new technologically advanced aliphatic resin adhesive, specifically developed for woodworking.
USES: Also known as carpenter's or yellow glue, ALCOLIN PROFESSIONAL WOOD GLUE is the choice adhesive for the Professional and DIY enthusiast, and is ideal for stress joints e.g. tables and chairs, restoration of antique furniture, model building, curved joints and supawood. ALCOLIN PROFESSIONAL WOOD GLUE gives excellent adhesion to porous substrates: Soft woods e.g. Pine, Meranti • Hard woods e.g. Imbuia, Oak • Processed board e.g. Hardboard, Chipboard, Supawood • Paper and Cardboard. Veneering—Also bonds felt, cloth, leather, and cork has numerous advantages over similar glues. It can be used to fill all types of cracks and holes on practically any surface including walls, plaster, cement and wood.

Pack Size: 250ml / 500ml Bottles with Applicator Nozzles CVR
RATE: 4/M2 PER LITER

TITEBOND WATERPROOF GLUE: is a revolutionary, one part moisture curing, solvent-free polyurethane adhesive with high bond strength, water and heat resistance.

USES: bonds a variety of substrates including all types of hard and soft wood, processed board, resin laminates (Formica, etc.), stone, concrete, metal, rigid PVC, ceramics, fiberglass, etc. ALCOLIN WATERPROOF GLUE is suitable for internal and external applications and is ideal for the manufacture and repair of windows and doors, shutters, furniture, gates, fences, garden rods, and other applications including marine applications. Also suitable for use on expanded polystyrene e.g. in cold rooms

Pack Size: 50 ml Tubes / 300 ml Cartridges
CVR RATE:

CONTACT SPRAY ADHESIVE: is a superior, all-purpose Polychloroprene rubber-based contact aerosol spray adhesive, with high bond strength. It bonds a variety of materials instantaneously on contact. The spray applicator allows for ease of use and for greater coverage of the adhesive.

USES: is ideal for household repairs, DIY tasks, handicrafts, flooring and upholstery applications. It can be used for bonding metals, rigid plastics, wood, concrete, stone, canvas, fabrics, cardboard, rubber, foam, cork, leather, etc.

Pack Size: 500 ml spray can
CVR RATE: Approx. 2,5 m2 per 500 ml (for a double-sided application)

SIKA PRO 2HP is a professional one component, thixotropic, polyurethane based joint sealant/adhesive. It cures under the influence of atmospheric moisture to form an elastomeric material with adhesive properties, in most cases without the need for priming of the substrate.

USES: Construction joints • Joints in precast concrete elements • External walling and chabbing joints • Infill panel joints • Curtain walling • Sanitary installations • Sealing around window and door frames • Flexible draught proofing • Sealing pen penetrations in walls or floors for ducts, piping, etc. • Restoring walls • New SikaFlex PRO 2HP bond with wet clean and SikaFlex PRO 2 • Excellent adhesion on all common basal materials, brick, ceramics, polyurethane epoxy, mort polyester, most metals and most timbers.

Pack Size: 310ml Cartridge Col: Grey, Black, White & Brown
RATE: see specifications

SPECIALISED PRODUCTS

p5

FASTSET: ALCOLIN RAPID EPOXY is a 2-part, CLEAR epoxy-based adhesive, which can be used easily and accurately due to its double syringe applicator.

USES: ALCOLIN RAPID EPOXY is particularly useful for bonding metal, stone, hard or soft woods, ceramics, porcelain, crystal, glass, ivory, precious stones and various plastic materials, such as polycarbonate, Formica and Bakelite to themselves and to other materials.

Pack Size: 24ml syringe
RATE: na

SIKADUR-30 is a thixotropic epoxy adhesive mortar based on a 2-component solvent-free epoxy resin. Sikadur-30 is used primarily to bond structural reinforcements to other substrates. It can also be used to bond and fill cracks & cavities

USES: Construction joints • Joints in precast concrete elements • External walling and chabbing joints • Infill panel joints • Curtain walling • Sanitary installations • Sealing around window and door frames • Flexible draught proofing • Sealing pen penetrations in walls or floors for ducts, piping, etc. • Restoring walls • New SikaFlex PRO 2HP bond with wet clean and SikaFlex PRO 2 • Excellent adhesion on all common basal materials, brick, ceramics, polyurethane epoxy, mort polyester, most metals and most timbers.

Pack Size: 1.2kg set CVR : see specification

3 COMPONENT EPOXY GROUT-A three component pourable epoxy grout based on high grade epoxy resin and specially graded aggregates. Mixes to a flowable grout. For use in heavy engineering and difficult conditions.

USES: Concrete in a high strength mortar with no shrinkage and suitable for grouting the following: • Bridge & retaining piles • Machine bases such as pumps, generators, motors, turbines etc. • Fixing bolts and anchors • Cast in situ base for reinforcement • Cast in situ concrete etc.

Pack Size: A+B+C 10kgs CVR : See specification

REPAIRTOUQ® Epoxy Putty Stick is a fast-setting polymer compound that mixes in just 1min to enable fast permanent repairs to many surfaces including metals, wood, glass, concrete, ceramics, fiberglass and many plastics

USES: Can be used in 1001 household and industrial applications: Repairs broken or loose wall and floor tiles, loose handrails, moldings, air conditioning ducts, ducts, levelling table and chair legs • Auto repairs such as bonding of trim, repairing of small dents, oil pans, small parts, filling rust holes, and thread locking • Mends toys, appliances, lawnmowers, sports equipment • Reshapes handles, knobs, broken nuts and bolts • Seals leaks in gutters, filling rust holes • Attaches fixtures, machine tags, signs, anchor bolts, screws, rods, machine housings • Patches chipped concrete, floors, bricks, blocks

Pack Size: 57g Twin Pack stick

QUICKWOOD® Epoxy Putty Stick is a fast-setting special polymer compound that mixes in just 1min to enable fast permanent repairs to wood. It also bonds metals, glass, concrete, ceramics, fiberglass, and many plastics.

USES: Can be used in 1001 household and industrial applications: Repairs broken or loose wall and floor tiles, loose handrails, moldings, air conditioning ducts, ducts, levelling table and chair legs • Auto repairs such as bonding of trim, filling rust holes, and thread locking • Mends toys, appliances, lawnmowers, sports equipment • Reshapes handles, knobs, broken nuts and bolts • Seals leaks in gutters, down pipes, filling rust holes • Attaches fixtures, machine tags, signs, anchor bolts, screws, rods, machine housings • Patches chipped concrete, floors, bricks, blocks

Pack Size: 56g Twin Pack stick

FASTITEL® Epoxy Putty Stick is a fast setting, industrial strength polymer compound that mixes in just one minute to enable fast permanent repairs to anything made of steel or other metals. It also bonds wood, glass, concrete, ceramics, fiberglass, and many plastics

USES: Rebuilding an air engine parts, fashioning handles • Sealing leaks, fills cracks and voids in metal, filling rust holes • Forming nuts and bolts, repair stripped threads • Repairs to metal bolts, equipment, ducts, housing and appliances, sink traps • Auto repairs such as bonding of trim, repairing small dents, oil pans, small parts, filling rust holes, and thread locking • attaching fixtures, machine tags, signs, anchor bolts, screws, rods, machine housings

Pack Size: 56g Twin Pack stick

AQUAMEND® Epoxy Putty Stick is a fast-setting, fibreglass reinforced polymer compound that mixes in just 1min to enable fast permanent repairs to many surfaces including fibreglass, concrete, glass, metals, wood, and many plastics. It is especially formulated to adhere to surfaces exposed to damp, wet or underwater (salt or fresh water) conditions

USES: Patching of things, scratches, cuts, gouges and holes in fibreglass, metal, and wooden boat decks and hulls • Repairs to fittings, pipes, electrical connections, leaking gaskets, water tanks, fish boxes, tubs, battery cases, sinks, spas, Jacuzzi, tanks and pools • Ideal for making emergency in-water repairs

Pack Size: 56g Twin Pack stick